

UTILIZATION OF BASALT FIBRE IN PAVER BLOCK

Ms. Deshmukh Anuja A, Ms. Gite Asha B, Ms. Nagar Kavita T,

Mr. Nikam Rohit S

Department of Civil, SIER Agaskhind, Nashik (India)

ABSTRACT

Interlocking Concrete Block Pavement (ICBP) technology has been introduced in India in construction, a decade ago, for specific requirement namely footpaths and parking areas etc. Now ICBP is being adopted extensively in different uses where the conventional construction of pavement using hot bituminous mix or cement concrete technology is not feasible or desirable. In this investigation, various properties such as compressive strength, split tensile strength, bending strength and water absorption of paver blocks consisting of crushed granite, unconventional materials such as kadapa and broken paver for various percentage replacements of coarse aggregate of fly ash, a waste product from thermal power plants, is a major problem in India. Many R&D and academic institutions are actively involved in the effective utilisation of fly ash in Civil Engineering applications. The Structural Engineering Research Centre (SERC), Chennai has carried out extensive research on utilisation of fly ash in concrete as partial cement replacement material (CRM) since 1975. Recently, SERC has carried out extensive R&D work on development of High Performance Concrete (HPC) mixes using fly ash (FA), ground granulated blast furnace slag (GGBS) and silica fume (SF) as mineral admixtures, especially to improve the durability characteristics of cement concrete. This paper presents the mechanical and durability properties of different HPC mixes containing fly ash. HPCs

Keywords: *Made from Basalt rock, High Tensile strength, Good electromagnetic, Resistance to acid, Low cost material.*

I. INTRODUCTION

Concrete paver blocks were first introduced in Holland in the nineteen fifties as replacement of paver bricks. Paver block is solid, unreinforced pre-cast cement concrete paving units used in the surface course of pavement. Paver block has been extensively used in many countries.

The first proposal to use concrete paving blocks highway pavement material in 1973, the development of design procedure has been conditioned by the need to persuade engineers that concrete blocks are effective structurally. Compared to pavements designed according to western European practice, British pavements are frequently deeper and more accurately specified

In the recent days, the various fibers develop and used in the construction, industrial and highway engineering. The steel is mainly used in that various application. Also fiber glass polythene fibers, carbon fibers, polyamide fibers are now developed and also used in construction, industrial and infrastructure development. In that list new one fiber is added, called, as basalt rock fibers.

II. PAVING BLOCK AND BASALT FIBRE

2.1 Paving Block: Interlocking Pavers are modern day solution to the outdoor flooring versatility in applications. They are high strength concrete moldings in various shapes, sizes & colors to suit the imagination of landscape architects & nature's essence. Interlocking pavers are manufactured concrete product that is individually placed in variety of patterns. Pavers do not use mortar or grout the sharp angle bedding sand that they are placed on provide the interlocking feature of pavers which allow them to shift slightly with the earth without cracking or breaking. Paving stones are three times stronger than poured in place concrete. Different colours of paver blocks available in market

The first proposal to use concrete paving blocks highway pavement material in 1973, the development of design procedure has been conditioned by the need to persuade engineers that concrete blocks are effective structurally. Compared to pavements designed according to western European practice, British pavements are frequently deeper and more accurately specified.

2.2 Basalt Fiber : In the recent days, the various fibers develop and used in the construction, industrial and highway engineering. The steel is mainly used in that various application. Also fiber glass polythene fibers, carbon fibers, polyamide fibers are now developed and also used in construction, industrial and infrastructure development. In that list new one fiber is added, called, as basalt rock fibers.

Basalt originates from volcanic magma and flood volcanoes, a very hot fluid or semi-fluid material under the earth crust, solidified in the open air. Basalt is the name given to a wide variety of volcanic rock, which is gray. Brown or dark in color, formed from volcanic lava after solidification.

The heavily thickened lavas contain olivine, clino-pyroxene (salite), plagioclase and opaque metal oxides. Paleocene and pyroxene make up 80% of many types of basalts. Because of good hardness and thermal properties, basalt has been used in the construction, industrial and highway engineering, in the form of crushed rock. It is used as surfacing and filling in roads, the floor tiles in the construction and as the lining material in the pipes for transporting the hot fluids. This can be major replacement to the asbestos, which possess health hazards by damaging respiratory systems.

However, it is not commonly known that basalt can be used in manufacturing and made into fine, superfine ultrafine fibers. Basalt is an alternative raw material for fiber forming because of its relatively homogeneous chemical structure, its large availability throughout the world, its freedom from impurities and of course, its ability to form fibers in the molten state.

Basalt fiber offer prospect of completely concrete. They have potential to high performance and cost effectively replace of fiberglass, steel new range of composite materials and product. Low cost high performance fibers offer potential to solve the largest problem in the cement and concrete industry, cracking and structural failure of concrete. They have potential to high performance and cost effectively replace of fiberglass, steel

III. IDENTIFICATION AND EQUATION

EQUATION

$f_{ck} = f'_{ck} + 1.65s \dots\dots\dots s = 5N/mm^2$

Total strength = 48.5N/mm²

Calculation :

Trail No.. 1 for 0%

Sample No.	Compressive Strength (N/mm ²)
1.	48.5
2.	47.7
3.	49

Trail No. 2 for 0.10%

Sample No.	Compressive Strength (N/mm ²)
1.	53.71
2.	54.1
3.	53.1

Trail No. 3 for 0.20%

Sample No.	Compressive Strength
1.	59.73
2.	58.8
3.	60.33

IV. FIGURES AND TABLES



Fig. No. 4.1 Paver blocks.



Fig. No.4.2BF roving



Fig.No 4.3 BF Filamen



Fig No.4.4 Basalt fibers mesh

Table No.4.1 Testing of cement

Sr. No.	Characteristics	Standard Value
1.	Normal consistency (%)	26%-33%
2.	Initial setting time (min.)	Not less than 30
3.	Final setting time (min)	Not less than 600
4.	Fineness (%)	<10

TableNo1.2 Properties of basalt fibre

Capability	Basalt fibre
Tensile strength, M Pa	3000 – 4840
Tensile strength, M Pa	3000 – 4840
Elastic modulus, G Pa	79.3 - 93.1
Elongation at break, %	3.1 – 6
Specific gravity	2.65 - 2.8

Diameter of filament, μm	6 - 21
Temperature of application, $^{\circ}\text{C}$	-260 - +500
Melting Temperature, $^{\circ}\text{C}$	1450

V. CONCLUSION

1. Addition of basalt fibre will increase properties of the paver block like compressive strength and satisfy limit of water absorption.
2. As % addition of basalt fibre to concrete increases there is increment in compressive strength.
3. A (0.40) addition to basalt fibre will increased compressive strength by 48.91%.
4. These fibres will most effective and economical in paver block use for heavy traffic areas.
5. Water absorption capacity is within permissible limit .
6. Basalt can be used in manufacturing and made into fine, superfine ultrafine fibers. Basalt is an alternative raw material for fiber forming because of its relatively homogeneous chemical structure, its large scale availability throughout the world, its freedom from impurities and of course, its ability to form fibers in the molten state.
7. Basalt Rock fibers have no toxic reaction with air or water, are non-combustible. When in contact with other chemicals they produce no chemical reactions that may damage health or the environment. So it is ecological friendly material.
8. Basalt rock fibers have new range of material in building construction, road construction, concrete industry and agriculture field. They have potential to high performance and cost effectively replace of fiberglass, steel and carbon fiber product in many applications. As per case study, concrete beam reinforced with BFRP bars achieved tensile strengths that are consisting with the relevant properties of the constituent materials. Concrete beams reinforced with BFRP bars behave in ductile manner exhibiting large deflection at failure.
9. Basalt is well known as a rock found in virtually every country round the world. Basalt rock is more in India (especially in Maharashtra). The cost of basalt is 10 times lower than that of raw materials for fiberglass.

VI. ACKNOWLEDGEMENT

I owe a great debt to a number of people who generously gave me so much of their precious time, their knowledge and their wisdom, and added whole dimensions to this thesis.

First and foremost, I express my deep sense of gratitude towards my guide Prof.D.R.Patil Asst Prof. Department of Civil Engineering, SIER Agashkind, for giving me the right direction, excellent references and taking keen interest in the project right from the beginning. They have been a constant source of motivation and inspiration. I have been benefited by their expertise a lot.

I express my sincere thanks to Prof. P.H. Khiarnar, & Head Department of Civil Engineering, S.I.E.R, Nashik for his co-operation and providing all required facilities to complete this course.

I owe this moment of satisfaction, with a deep sense of gratitude to Prof. J.J.CHOPADE ,Principal of S.I.E.R, Nasik for helping me to complete the project work relatively easier and better...

I extend my sincere regards and heartfelt gratitude to my Parents and family members for their love, care, support, and encouragement in all my endeavors and also for the pains they always take happily for me. They have been a source of inspiration throughout and without their support, no milestone was ever achievable.

Last but not least I would like to acknowledgemy friends, and all my Colleagues for their constant support and encouragement in making my project a success and all those persons who directly and indirectly contributed to the completion of project.

REFERENCES

- [1.] Brian Shackel ; “ The Challenges of Concrete Block Paving As a Muture Technologies”. University of New South Wales, Sydney, Australia.
- [2.] Dixit n. Patel ; Jayeshkumar r. Pitroda ; (2014) “Techno economical developm ent of low-cost interlocking Paverblock by partially replacement of portland pozzolana Cement with used foundry sand waste” M.B.V.M. Engineering College, Vallabh Vidyanagar. Gujarat, India. Volume 2, Issue 4.
- [3.] Dr. M. C. Nataraja ; “Fiber Reinforced Concrete Behaviour Properties And Application”. Sri Jayachamarajendra College of Engineering, Mysore.
- [4.] Dr. Richard Parnas ; PI, Dr. Montgomery Shaw ; (2007) “Basalt Fiber Reinforced Polymer Composites”.
- [5.] Ganesh Tapkire ; Satish Parihar ; Pramod Patil ; Hemraj Kumavat ; (2014) “Recycled Plastic Used In Concrete Paver Blocks”. NRI Institute of Research and Technology, Bhopal, India. Volume 03 , Issue 09.
- [6.] IS 10262:2009,-Concrete Mix Proportioning-Guidelines, Bureau Of Indian Standard, New Delhi,2009.
- [7.] IS 15658:2006- Precast concrete blocks for paving-Specification, Bureau Of Indian Standard, New Delhi,2006.
- [8.] IS 456:2000, —Indian Standard plain and reinforced concrete-Code of Practice|| , Bureau of Indian Standards, New Delhi, 2000.
- [9.] J. A. Peter ; M. S.Gopalakrishnan ; “Utilisation Of Flyash As Cement Replacement Material To Produce High Performance Concrete”. Structural Engineering Research Centre, CSIR Campus, Taramani, Chennai.
- [10.] 10. J. Knapton ; S.D. Barber ; “UK Research Into Concrete Block Pavement Design”. University of Newcastle upon Tyne, England.
- [11.] M. C. Nataraja ; Lelin Das ; “CA Study On The Strength Properties Of paver Blocks Made From Unconventional Material ”.Sri Jayachamarajendra College of Engineering, Mysore.
- [12.] Michael Lazar ; John Emery; (2002) “Reflective Pavers And Kerbs”. Acme Paving consultants Pvt.Ltd. Singapore.
- [13.] Osman Gencil ; Cengiz Ozelb ; Fuat Koksalc ; Ertugrul Erdogmus ; Gonzalo Martínez-Barrerae ; Witold Brostow ; (2012) “Properties of concrete paving blocks made with waste marble” Bartin University, 74100 Bartin, Turkey.